

## PVC-Schlauch mit Gewebeeinlage DIFLEX



Beschreibung					
Artikelnummer	Ø Innen./Außen. (mm)	Rollen (m)	Biegeradius (mm)	Max. Betriebsdruck (bar)	Farbe
<b>DIFLEX 6</b>	6 x 12	50	36	15	Blau
<b>DIFLEX 8</b>	8 x 14	50	54	15	Blau
<b>DIFLEX 8RG</b>	8 x 14	50	54	15	Rot
<b>DIFLEX 8C25</b>	8 x 14	25	54	15	Blau
<b>DIFLEX 9</b>	9 x 15	50	66	15	Blau
<b>DIFLEX 10</b>	10 x 16	50	74	15	Blau
<b>DIFLEX 10RG</b>	10 x 16	50	74	15	Rot
<b>DIFLEX 10C25</b>	10 x 16	25	74	15	Blau
<b>DIFLEX 12</b>	12 x 19	50	90	15	Blau
<b>DIFLEX 12RG</b>	12 x 19	50	90	15	Rot
<b>DIFLEX 13</b>	13 x 20	50	101	15	Blau
<b>DIFLEX 13RG</b>	13 x 20	50	101	15	Rot
<b>DIFLEX 16</b>	16 x 22	25	145	15	Blau

Artikelnummer	Ø Innen./Außen. (mm)	Rollen (m)	Biegeradius (mm)	Max. Betriebsdruck (bar)	Farbe
<b>DIFLEX 19</b>	19 x 26	25	174	15	Blau
<b>DIFLEX 25</b>	25 x 33	25	260	15	Blau
<b>DIFLEX 32</b>	32 x 42	25	320	12	Durchsichtig
<b>DIFLEX 38</b>	38 x 48	25	420	11	Durchsichtig
<b>DIFLEX 50</b>	50 x 64	25	600	8	Durchsichtig

